

Jabco Lite Flush Belt Replacement – 58500 Series

EN - Isolate the power supply to the toilet system - Close inlet and outlet seacocks before carrying out maintenance.

SE - Koppla bort strömförsörjningen till toaletten - Stäng både in- och utlopps bottenförskruvningar


ES - Aislar el retrete de la fuente de alimentación – Cerrar los grifos de fondo (entrada y salida)

DE - Trennen Sie die Stromversorgung der Toilette - Schließen Sie die Einlass- und Auslass-Seeventile


FR - Débranchez l'alimentation électrique du toilette - Fermez les vannes d'arrivée et d'évacuation

IT - Scollegare l'alimentazione elettrica della toilet - Chiudere i condotti di ingresso e uscita della presa a mare

NL - Ontkoppel de stroomtoevoer naar het toilet - Sluit inlaat- en uitlaatdoorvoerkransen




Tools Required



Phillips

Pozidrive



1. Remove clips & hose




2. Remove screws



3. Twist & lift bowl




4. Remove screws



5. Remove pump




6. Remove screws




7. Turn clip 90° and remove



8. Remove pump



9. Remove screws




10. Remove screws



11. Tilt motor



12. Replace belt – do not use tools



13. Replace cover and screws



14. Replace waste pump



15. Replace rinse pump & control box



16. Reassemble toilet



EN - Test System
FR - Système de test
IT - Sistema di prova
DE - Prüfsystem
SE - Testsystem
ES - Sistema de prueba
NL - Test system



43010-0643
Revision A